Technical Data Sheet (TDS)

FireBløk Gasket



Protect the small openings that can compromise a fire-rated wall.

The FireBlok Firestop Gasket is an intumescent thermoplastic electrical box insert used as a membrane penetration firestop to maintain the fire-resistant ratings of 1- and 2-hour fire walls.

The insert is certified for both 1 & 2 hour, U300, U400, V400 and U411 wall assemblies with metal electrical boxes with plastic or metal cover plates according to the ASTM E119/E814 standards for fire resistive wall openings.

Specifications	
Size	3-3/4 in. x 3-3/4 in. x 3/8 in.
Volume	2.1 cu. in.
Colour	White
Standard Package	30
Master Carton	120

Technical Data Sheet (TDS)

FireBløk Gasket

Features
Tool-free, peel-and-stick installation
Expansion begins @ 300°F / 148°C
Highly Intumescent (20+ times its original size)
Certified for both 1 & 2 Hour fire rated wall
Soundproof with a STC Rating 52*
Pre-Molded Ground Screw Openings
Certified for both Plastic and Metal faceplates in all fire-rated walls
Pre-Scored on the back for easy snapping and installation
Warranted for the life of the building when stored below 130°F / 54°C
Adheres to back of electrical box
Tested to ASTM E90 Standard

Additional information about FireBlok Gasket available on our website

Learn More

Buy FireBlok Gasket

Learn More



Pyrophobic® Systems Ltd.

649 Welham Road, Barrie ON, L4N 0B7 | +1.705.730.0840 | pyrophobic.com

July 2026